



**INTERNATIONAL EQUIPMENT COMPONENTS, INC.**

Phone: **562.597.4533** eMail: **sales@iec-corp.com**

Web: **www.levelingmounts.com & www.iec-corp.com**

## TUBE CAPS & PLUGS

### ROUND

### Tube Caps — Round

These rugged, *black polyethylene round tube caps* (plug type) are designed to fit inside tubing for both feet and cap applications. The ribbed fins provide a positive fit inside the tube to fit a variety of wall thicknesses without falling out. The textured top resists scratches and scarring. Glossy finish also available.



#### Measure the outside tube dimension to order from our spec sheet.

Measuring the inside dimension as well, will help us to recommend the right plug for your application, especially if you have thick wall tubing or pipe. ABS available upon special request on some sizes.

For solid legs, use the OD cap shown on the following pages. For angled leg applications, we recommend the domed caps, ball cap or swivel glides also shown later in this catalog section.

White (-WH) available on 3/4", 1", 1-1/4" and 1-1/2" sizes. Tubing gauge refers to the wall thickness. 18 GA is thin wall (.05") and 5 GA is thick (.21"). Wall thickness is equal to the OD of the tube, minus the ID then divide by 2 (or measure directly using calipers).

### TUBE CAPS — ROUND

P/N (round)	Tubing O.D.	Tubing Gauge
IL24D-CAP-RD	3/8	19
IL24C-CAP-RD	1/2	16-20
IL24B-CAP-RD	5/8	14-20
IL24A-CAP-RD	3/4	14-20
IL24-CAP-RD	7/8	14-20
IL25-CAP-RD	1	14-20
IL25A-CAP-RD	1-1/8	14-18
IL26-CAP-RD	1-1/4	11-19
IL26A-CAP-RD	1-3/8	14-18
IL27-CAP-RD	1-1/2	11-19
IL27B2-CAP-RD	1-5/8	11-19
IL27B-CAP-RD	1-3/4	11-19
IL27B3-CAP-RD	1-7/8	11-19
IL27A-CAP-RD	2	11-19
IL27A2-CAP-RD	2-1/4	14-20
IL27A3-CAP-RD	2-3/8	10-14
IL27C-CAP-RD	2-1/2	14-20
IL27E-CAP-RD	2-3/4	7-14
IL27E2-CAP-RD	2-7/8	4-7
IL27F-CAP-RD	3	8-14
IL27F-CAP-RD-8	3	8-12
IL27H-CAP-RD	3-1/2	6-13
IL27K-CAP-RD	4	8-14
IL27K-CAP-RD-5	4	5-11
IL27K2-CAP-RD	4-1/2	7-11
IL27M-CAP-RD	4-3/4	6-11

TUBE GAUGE	18	16	14	12	10	8	6	4
WALL THICKNESS	.05	.06	.08	.10	.135	.165	.195	.225